
```

% Computer Lab 7
% Exercise 1
h = 0.001;
M = 1000; % number of simulations/paths per value of h
mu = 0.06; % = r
K = 105;
T = 1;
sigma = 0.15;
X_0 = 100;
N = round(T./h); % number of grid points per simulation
payoffs = zeros(M,1); % for MC estimator
for jj = 1:M
    X = zeros(N,1); % vector to store the path
    dB = sqrt(h).*randn(N,1); % Brownian increments
    X(1,1) = X_0;
    % simulate the path of X using the EM scheme
    for n = 1:N-1
        X(n+1,1) = X(n,1) + h*mu*X(n,1) + sigma*X(n,1)*dB(n+1,1);
    end
    payoffs(jj,1) = exp(-mu*T)*max(X(N,1)-K,0);
end
% parts (a) and (b)
% Comparing simulated price to the closed form solution (see page 59
% of the
% notes for details)
simulated_prices = mean(payoffs)
true_price = BS_price(X_0,mu,sigma,T,K)

% part (c)
% Using CLT approximation to produce 95% confidence interval for the
% computed prices
% NB the true price will fall within the computed confidence interval
% approximately 95% of the time - this is testable....
mu_hat = simulated_prices;
sigma_hat = sqrt(var(payoffs));
lower = mu_hat - 1.96*sigma_hat/sqrt(M)
upper = mu_hat + 1.96*sigma_hat/sqrt(M)

simulated_prices =

    6.616914689906403

true_price =

    6.519131435976362

lower =

    6.003487191720272

```

`upper =`

`7.230342188092534`

Published with MATLAB® R2015a